

MDE Semiconductor, Inc. Circuit Protection Products

78-150 Calle Tampico, Unit 210, La Quinta, CA., USA 92253 Tel: 760-564-8656 • Fax: 760-564-241
1-800-831-4881 Email: sales@mdesemiconductor.com Web: www.mdesemiconductor.com

Metal Oxide Varistors

HIGH ENERGY D SERIES

Varistor Voltage	25 mm	32 mm	40 mm	53 mm
200	MDE-25D201K	MDE-32D201K	MDE-40D201K	MDE-53D201K
220	MDE-25D221K	MDE-32D221K	MDE-40D221K	MDE-53D221K
240	MDE-25D241K	MDE-32D241K	MDE-40D241K	MDE-53D241K
270	MDE-25D271K	MDE-32D271K	MDE-40D271K	MDE-53D271K
300	MDE-25D301K	MDE-32D301K	MDE-40D301K	MDE-53D301K
330	MDE-25D331K	MDE-32D331K	MDE-40D331K	MDE-53D331K
360	MDE-25D361K	MDE-32D361K	MDE-40D361K	MDE-53D361K
390	MDE-25D391K	MDE-32D391K	MDE-40D391K	MDE-53D391K
430	MDE-25D431K	MDE-32D431K	MDE-40D431K	MDE-53D431K
470	MDE-25D471K	MDE-32D471K	MDE-40D471K	MDE-53D471K
510	MDE-25D511K	MDE-32D511K	MDE-40D511K	MDE-53D511K
560	MDE-25D561K	MDE-32D561K	MDE-40D561K	MDE-53D561K
620	MDE-25D621K	MDE-32D621K	MDE-40D621K	MDE-53D621K
680	MDE-25D681K	MDE-32D681K	MDE-40D681K	MDE-53D681K
750	MDE-25D751K	MDE-32D751K	MDE-40D751K	MDE-53D751K
780	MDE-25D781K	MDE-32D781K	MDE-40D781K	MDE-53D781K
820	MDE-25D821K	MDE-32D821K	MDE-40D821K	MDE-53D821K
910	MDE-25D911K	MDE-32D911K	MDE-40D911K	MDE-53D911K
950	MDE-25D951K	MDE-32D951K	MDE-40D951K	MDE-53D951K
1000	MDE-25D102K	MDE-32D102K	MDE-40D102K	MDE-53D102K
1100	MDE-25D112K	MDE-32D112K	MDE-40D112K	MDE-53D112K
1200	MDE-25D122K	MDE-32D122K	MDE-40D122K	MDE-53D122K
1800	MDE-25D182K	MDE-32D182K	MDE-40D182K	MDE-53D182K

Varistor Voltage: Test Current is DC 1mA

Temperature range: -40°C ~ 85°C

Storage temperature: -40°C ~ 125°C

Temperature Coefficient of voltage: -0.05%/°C