

MDE Semiconductor, Inc.

78-150 Calle Tampico, Unit 210, La Quinta, CA. U.S.A. 92253 Tel: 760-564-8656 • Fax: 760-564-2414

1-800-831-4881 Email: sales@mdesemiconductor.com Web: www.mdesemiconductor.com


MAX20KA Cell Series

Surface Mount Transient Voltage Suppressor

Stand-off Voltage 16 to 66 Volts

FEATURES

- Glass passivated junction
- Bi-directional
- RoHS Compliant
- 20KA surge capability at 8 x 20µsec waveform
(per IEC-61000-4-5)
- Excellent clamping capability
- Flammability Classification 94V-0
- Operating and storage Temp -40°C to +125°C



See Dimensions on Page 2

MECHANICAL DATA

Cell: CU wth Ag Plating

Mounting Position: Any

Weight: 8.0 ± 1g

DEVICES FOR BIPOLAR APPLICATIONS

Bidirectional use C or CA Suffix. Electrical characteristics apply in both directions.

MAXIMUM RATINGS AND CHARACTERISTICS

PART NUMBER	REVERSE STAND-OFF VOLTAGE $V_{RWM}(V)$	BREAKDOWN VOLTAGE $V_{BR}(V)$ MIN. @ I_T	BREAKDOWN VOLTAGE $V_{BR}(V)$ MAX. @ I_T	TEST CURRENT I_T (mA)	MAXIMUM CLAMPING VOLTAGE @ I_{PP} $V_C(V)$				REVERSE LEAKAGE @ V_{RWM} $I_R(\mu A)$
					V_{CL} (8/20 μS) Volts	I_{PP} (8/20 μS) Amps	V_{CL} (10/350 μS) Volts	I_{PP} (10/350 μS) Amps	
MAX20KA-016CA CELL	16.0	17.50	19.30	10	30	20,000	28	3,200	5
MAX20KA-022CA CELL	22.0	23.75	26.25	10	42	20,000	40	3,200	5
MAX20KA-058CA CELL	58.0	64.00	70.00	10	120	20,000	107	3,200	5
MAX20KA-063CA CELL	63.0	68.00	75.00	10	125	20,000	110	3,200	5
MAX20KA-066CA CELL	66.0	72.00	80.00	10	130	20,000	120	3,200	5

NOTE 1 : Using 8x20µS Wave shape defined in IEC 61000-4-5

MDE Semiconductor, Inc.

78-150 Calle Tampico, Unit 210, La Quinta, CA. U.S.A. 92253 Tel: 760-564-8656 • Fax: 760-564-2414

1-800-831-4881 Email: sales@mdesemiconductor.com Web: www.mdesemiconductor.com

MAX20KA Cell Series

Surface Mount Transient Voltage Suppressor

Stand-off Voltage 16-66 Volts

Ratings and Characteristic Curves (TA=25°C unless otherwise noted)

Fig.1 - Test Pulse Waveform




Fig.2 - Pulse Derating Curve

